

*Dispose of oil-soaked rags and protect your establishment from fires due to:*

- spontaneous combustion
- sparks
- careless use of smoking material

**US OSHA Compliant Oily Waste Cans** are essential whenever solvent cloths and wiping rags are used. Rags and cloths soaked with solvents, thinners, linseed oil, combustible adhesives and other flammable liquids present a serious fire risk when improperly discarded. The specially designed lid opens no more than 60 degrees and stays closed when not in use, isolating contents from fire sources and limiting oxygen so spontaneous combustion risk is virtually eliminated. Round construction and elevated base encourage circulation of air around can to disperse heat and reduce moisture build-up and rusting.



Carry handle for portability.

A variety of sizes accommodate your specific need. Choose either red or yellow, or both when colour identification is desired to help segregate materials or to differentiate departments within location sites. All feature galvanised steel body construction with a durable powder-paint finish. Most sizes are also offered with a hand-operated cover if preferred.

Foot-operated cover leaves hands free.

## Oily Waste Cans

Description and Capacity	Dimensions Outer Dia x H	Approv/Lstg Regulation	Red Can Model No	Yellow Can Model No	Delvr Wt (kg)
8 litre countertop oily waste can	244 x 232 mm	FM	09200	09200Y	3.0
23 litre oily waste can with foot-operated cover	302 x 403 mm	FM,UL	09100	09101	5.0
38 litre oily waste can with foot-operated cover	354 x 464 mm	FM,UL	09300	09301	5.0
53 litre oily waste can with foot-operated cover	408 x 514 mm	FM,UL	09500	09501	7.0
79 litre oily waste can with foot-operated cover	467 x 595 mm	FM,UL	09700	09701	10.0

Call Your Local Distributor Today!

[www.justritemfg.com](http://www.justritemfg.com)

